



CHAIN SLINGS > 2 LEG ADJUSTABLE

# 1/2" x 15' Adjustable 2 Leg Chain Sling w/ Self-Locking Hooks - Grade 100

SKU: 12G100DOSLA-15 Item weight: 95.19 lbs

|            |        |             |
|------------|--------|-------------|
| CHAIN SIZE | LENGTH | CAPACITY    |
| 1/2"       | 15'    | 15,000 lbs. |

## SPECIFICATIONS

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| SKU                | 12G100DOSLA-15                                                                        |
| Safety Factor      | 4:1                                                                                   |
| 30 Degree Capacity | 15,000 lbs.                                                                           |
| 45 Degree Capacity | 21,200 lbs.                                                                           |
| 60 Degree Capacity | 26,000 lbs.                                                                           |
| Length             | 15'                                                                                   |
| Chain Size         | 1/2"                                                                                  |
| End Fitting        | Self-Locking                                                                          |
| Product Weight     | 95.19 lbs.                                                                            |
| Standards          | Meets or exceeds all ASTM A906 / A906M & ASME B30.10 requirements.<br>AWRF Accredited |
| Manufacturer Name  | KWB                                                                                   |
| Additional Info    | Items are made to order and most ship same day - exceptions apply to large orders.    |

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.



Current price & availability: [heavyhaulrigging.com/p/1-2-x-15-adjustable-2-leg-chain-sling-w-self-locking-hooks-grade-100](https://heavyhaulrigging.com/p/1-2-x-15-adjustable-2-leg-chain-sling-w-self-locking-hooks-grade-100)