

L-TRACK > L-TRACK FITTINGS

Double Stud L-track Fitting with Pear Link | 5,000 lbs. BS | 4-Pack

SKU: 1519-DSR-4PK Item weight: 1.6 lbs

WORKING LOAD LIMIT	BREAK STRENGTH
1,666 lbs.	5,500 lbs.

SPECIFICATIONS

SKU	1519-DSR-4PK
Working Load Limit (lbs.)	1,666 lbs.
Assembly Break Strength	5,500 lbs.
Finish	Zinc-Plated
Type	Double Stud
Product Weight	1.52 lbs.
Quantity	4-Pack
Additional Info	Fits all L-track

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/double-stud-l-track-fitting-w-pear-link-5-000-lb-break-strength-4-pack