

CHAIN SLINGS > 2 LEG

3/8" x 14' 2 Leg Chain Sling w/ Foundry Hooks - Grade 100

SKU: 38G100DOF-14 Item weight: 48.73 lbs

|            |        |            |
|------------|--------|------------|
| CHAIN SIZE | LENGTH | CAPACITY   |
| 3/8"       | 14'    | 8,800 lbs. |

SPECIFICATIONS

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| SKU                | 38G100DOF-14                                                                          |
| Safety Factor      | 4:1                                                                                   |
| 30 Degree Capacity | 8,800 lbs.                                                                            |
| 45 Degree Capacity | 12,400 lbs.                                                                           |
| 60 Degree Capacity | 15,200 lbs.                                                                           |
| Length             | 14'                                                                                   |
| Chain Size         | 3/8"                                                                                  |
| End Fitting        | Foundry                                                                               |
| Product Weight     | 48.73 lbs.                                                                            |
| Standards          | Meets or exceeds all ASTM A906 / A906M & ASME B30.10 requirements.<br>AWRF Accredited |
| Manufacturer Name  | KWB                                                                                   |
| Additional Info    | Made to order.                                                                        |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/3-8-x-14-2-leg-chain-sling-w-foundry-hooks-grade-100](https://heavyhaulrigging.com/p/3-8-x-14-2-leg-chain-sling-w-foundry-hooks-grade-100)