

WIRE ROPE > 7X19 STAINLESS TYPE 304 WIRE ROPE

3/16" 7x19 Stainless Steel Aircraft Cable - Type 304 | Linear Foot

SKU: 719SSAC304-316 Item weight: 0.06 lbs

|                        |                     |        |
|------------------------|---------------------|--------|
| BREAK STRENGTH         | GRADE               | LENGTH |
| 1.85 tons / 3,700 lbs. | 304 Stainless Steel | 1'     |

SPECIFICATIONS

|                            |                                                                                                                    |
|----------------------------|--------------------------------------------------------------------------------------------------------------------|
| SKU                        | 719SSAC304-316                                                                                                     |
| Assembly Break Strength    | 1.85 tons / 3,700 lbs.                                                                                             |
| Rated for Overhead Lifting | Yes                                                                                                                |
| Grade                      | 304 Stainless Steel                                                                                                |
| Wire Rope Diameter         | 3/16"                                                                                                              |
| Length                     | 1'                                                                                                                 |
| Wire Rope Class            | 7x19                                                                                                               |
| Product Weight             | 0.07 lbs.                                                                                                          |
| Weight Per Foot            | 0.07                                                                                                               |
| Standards                  | Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023 |
| Additional Info            | Right Hand Regular Lay Not intended for Aircraft Use                                                               |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: [heavyhaulrigging.com/p/3-16-7x19-type-304-stainless-steel-wire-by-linear-foot](https://heavyhaulrigging.com/p/3-16-7x19-type-304-stainless-steel-wire-by-linear-foot)