

CHAIN SLINGS > 3 LEG ADJUSTABLE

9/32" x 10' Adjustable 3 Leg Chain Sling w/ Self-Locking Hooks - Grade 100

SKU: 932G100TOSLA-10 Item weight: 33.93 lbs

|            |        |            |
|------------|--------|------------|
| CHAIN SIZE | LENGTH | CAPACITY   |
| 9/32"      | 10'    | 6,400 lbs. |

SPECIFICATIONS

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| SKU                | 932G100TOSLA-10                                                                       |
| Safety Factor      | 4:1                                                                                   |
| 30 Degree Capacity | 6,400 lbs.                                                                            |
| 45 Degree Capacity | 9,100 lbs.                                                                            |
| 60 Degree Capacity | 11,200 lbs.                                                                           |
| Length             | 10'                                                                                   |
| Chain Size         | 9/32"                                                                                 |
| End Fitting        | Self-Locking                                                                          |
| Product Weight     | 33.93 lbs.                                                                            |
| Standards          | Meets or exceeds all ASTM A906 / A906M & ASME B30.10 requirements.<br>AWRF Accredited |
| Manufacturer Name  | KWB                                                                                   |
| Additional Info    | Made to order.                                                                        |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/9-32-x-10-adjustable-3-leg-chain-sling-w-self-locking-hooks-grade-100](https://heavyhaulrigging.com/p/9-32-x-10-adjustable-3-leg-chain-sling-w-self-locking-hooks-grade-100)