

LIFTING BEAMS AND SPREADER BARS > DURA-LITE 416 ADJUSTABLE BEAM

Caldwell 1 Ton x 2 - 3' Adjustable Lifting Beam | Dura-Lite 416-1-3

SKU: CASLB2000-3 Item weight: 20 lbs

WORKING LOAD LIMIT	MATERIAL
2,204 lbs.	Fiber-Reinforced Polymer Composite

SPECIFICATIONS

SKU	CASLB2000-3
Working Load Limit (lbs.)	2,204 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Throat Opening	0.91"
Spread	2' - 3'
Bail Dimensions	Inside Width: 2.8" Inside Length: 4.5" Diameter: 0.62"
End Fitting	Bottom Swivel Latch Hooks & Top Link Included
Material	Fiber-Reinforced Polymer Composite
Finish	Acrylic Polyurethane
Product Weight	20 lbs.
Standards	Complies with ASME B30.9, BTH-1, and B30.20, design category B, service class 4 regulations.
Manufacturer Name	Caldwell
Brand Part Number	416-1-3
Additional Info	WLL (tons): 1 Headroom: 20.4" Bail Adjustment Length: 6" Bail Adjustment Increments: 3"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/dura-lite-composite-adjustable-spreader-lifting-beam-2-000-lb-capaci...