

MOVING SUPPLIES > PACKAGING SUPPLIES

5/8" Cordstrap Buckles for Composite Strapping - Pallet

SKU: CB5S-CS-PLT Item weight: 2,185.6 lbs

BREAK STRENGTH	GRADE	MATERIAL
1940 lbf	DNV Witnessed	Galvanized Steel Wire

SPECIFICATIONS

SKU	CB5S-CS-PLT
Assembly Break Strength	1940 lbf
Grade	DNV Witnessed
Size	5/8"
Material	Galvanized Steel Wire
Finish	Galvanized
Type	Galvanized Buckles for Composite Cord Strapping
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	2176 lbs.
Brand	Cordstrap
Brand Part Number	7373000
Quantity	64-Pack (Pallet)
Additional Info	System Breaking Strength: 1940 lbf Linear Breaking Strength: 1212 lbf Elongation at break: 12% Recommended Tensioners: CT20 & CTT20

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/5-8-cordstrap-buckles-for-composite-strapping-pallet