

MOVING SUPPLIES > PACKAGING SUPPLIES

Cordstrap 1/2" x 3610' Composite Corded Strapping - 2-Pack

SKU: CC40-CS-2PK Item weight: 46.6 lbs

BREAK STRENGTH	GRADE	LENGTH	MATERIAL
1058 lbf	DNV Witnessed	3608' per roll	High tenacity p...

SPECIFICATIONS

SKU	CC40-CS-2PK
Assembly Break Strength	1058 lbf
Grade	DNV Witnessed
Size	1/2"
Length	3608' per roll
Core	8" Diameter
Material	High tenacity polyester filament yarn and homopolymer polypropylene
Color	White
Type	Composite Cord Strapping
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	25.83 lbs.
Brand	Cordstrap
Brand Part Number	7251000
Quantity	2-Pack
Additional Info	System Breaking Strength: 1058 lbf Linear Breaking Strength: 661 lbf Elongation at break: 12% Recommended Tensioners: CT20 & CTT20

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/cordstrap-1-2-x-3610-composite-corded-strapping-2-pack