

FALL PROTECTION > HARNESSES & BODY WEAR

FallTech ComforTech GEL Full-Body Construction
Harness w/ Trauma Straps | Belted | L | 7081BL

SKU: FPBW-7081BL Item weight: 6.3 lbs

MATERIAL

D-ring: Aluminum alloy; 5,000 lb min. static strength Webbing: Polyester; 5,000 l...

SPECIFICATIONS

SKU	FPBW-7081BL
Size	L
Material	D-ring: Aluminum alloy; 5,000 lb min. static strength Webbing: Polyester; 5,000 lb min. static strength Buckles / Adjusters: Aluminum alloy and plated alloy steel; 3,372 lb min. static strength
Color	Gold
Style	Belted
Type	Fall Arrest and Work Positioning, 3D
Product Weight	6.3 lbs.
Standards	ANSI Standards: ANSI Z359.11-2014, OSHA Standards: OSHA 1926.502 and 1910.140, CSA Standards: CSA Z59.10-2018
Manufacturer Name	FallTech
Brand	Advanced ComforTech® Gel
Brand Part Number	7081BL
Additional Info	OSHA User Capacity: 130 to 425 lb max. ANSI User Capacity: 130 to 310 lb max. Static Strength: 3,600 lb min.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/falltech-comfortech-gel-full-body-construction-harness-w-trauma-str...