

FALL PROTECTION > HARNESSES & BODY WEAR

FallTech FT-Iron Construction Full-Body Harness | Belted
| XS | 8144XS

SKU: FPBW-8144XS Item weight: 5.2 lbs

MATERIAL

D-ring: Aluminum alloy; 5,000 lb min. static strength Webbing: Polyester; 5,000 l...

SPECIFICATIONS

SKU	FPBW-8144XS
Size	XS
Material	D-ring: Aluminum alloy; 5,000 lb min. static strength Webbing: Polyester; 5,000 lb min. static strength Buckles / Adjusters: Aluminum alloy and plated alloy steel; 3,372 lb min. static strength
Color	Black
Style	Belted
Type	Fall Arrest and Work Positioning, 3D
Product Weight	5.2 lbs.
Standards	ANSI Standards: ANSI Z359.11-2021, OSHA Standards: OSHA 1926.502 and 1910.140, CSA Standards: CSA Z259.10-2018
Manufacturer Name	FallTech
Brand	FT-Iron™
Brand Part Number	8144XS
Additional Info	OSHA User Capacity: 133 to 425 lb max. ANSI User Capacity: 133 to 310 lb max. Static Strength: 3,600 lb min. Horizontal Leg Straps

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/falltech-ft-iron-construction-full-body-harness-belted-xs-8144xs