

EYE BOLTS > GALVANIZED SHOULDER EYE BOLTS

5/16" x 2-1/4" Galvanized Shoulder Eye Bolt

SKU: GVSEB516X2-14 Item weight: 0.11 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	WIDTH	LENGTH
1,200 lbs.	6000 lbs.	0.69"	2-1/4"

SPECIFICATIONS

SKU	GVSEB516X2-14
Working Load Limit (lbs.)	1,200 lbs.
Assembly Break Strength	6000 lbs.
Diameter	5/16"
Width	0.69"
Shank Length	2-1/4"
Material	Steel
Finish	Galvanized
Product Weight	.1 lbs.
Standards	Meets or exceeds ASTM F541 requirements.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/5-16-x-2-1-4-galvanized-shoulder-eye-bolt