

TURNBUCKLES > GALVANIZED HOOK & HOOK

1/2" x 12" Hook & Hook Galvanized Turnbuckle

SKU: HHTBGV12X12 Item weight: 2.18 lbs

WORKING LOAD LIMIT	LENGTH
1,500 lbs.	19.38"

SPECIFICATIONS

SKU	HHTBGV12X12
Working Load Limit (lbs.)	1,500 lbs.
Safety Factor	5:1
Rated for Overhead Lifting	No
Diameter	1/2"
Length Closed	19.38"
Length Open	32.5"
Body Length	12"
Turnbuckle Size	1/2" x 12"
Finish	Galvanized
Product Weight	2.1 lbs.
Standards	Meets or exceeds all requirements of ASTM F-1145.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- NOT FOR OVERHEAD LIFTING. This product is rated for cargo securement only.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/galvanized-turnbuckle-hook-hook-1-2-x-12