

LIFTING BEAMS AND SPREADER BARS > STANDARD ADJUSTABLE W/ SHACKLES

Standard Adjustable Lifting Beam w/ Shackles - 15,000 Lb. Capacity - 6' to 12' Spread

SKU: LBAHA15K144 Item weight: 845 lbs

WORKING LOAD LIMIT	MATERIAL
15,000 lbs.	Steel

SPECIFICATIONS

SKU	LBAHA15K144
Working Load Limit (lbs.)	15,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Spread	6' - 12'
Bail Dimensions	Inside Width: 4" Inside Length: 7" Top Thickness: 2" Thickness: 1"
End Fitting	Bottom Shackles Included
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	830 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	15128
Additional Info	WLL (tons): 7.5 Headroom: 23.7" Bail Adjustment Length: 24" Bail Adjustment Increments: 3" Spread Increments: 3"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/standard-adjustable-lifting-beam-w-shackles-15-000-lb-capacity-6-to-...