

LIFTING BEAMS AND SPREADER BARS > LOW HEADROOM ADJUSTABLE

Low Headroom Adjustable Lifting Beam | 4,000 lb. Capacity | 15' to 20' Spread

SKU: LBLHA4K20 Item weight: 1,115 lbs

WORKING LOAD LIMIT	LENGTH	MATERIAL
4,000 lbs.	246.5"	Steel

SPECIFICATIONS

SKU	LBLHA4K20
Working Load Limit (lbs.)	4,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Overall Length	246.5"
Spread	15' - 20'
Bail Dimensions	Inside Width: 3" Inside Length: 5" Top Thickness: 0.88" Thickness: 0.75"
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	1115 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	22155

Additional Info	WLL (tons): 2 Headroom: 17" Spread Adjustment Increments: 6" per side
-----------------	---

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/low-headroom-adjustable-lifting-beam-4-000-lb-capacity-15-to-20-spr...