

LIFTING BEAMS AND SPREADER BARS > NON CONDUCTIVE

Non-Conductive Lifting Beam - 4,000 Lb. Capacity - 2.5' Max Spread

SKU: LBNC4K1830 Item weight: 86 lbs

WORKING LOAD LIMIT	LENGTH	MATERIAL
4,000 lbs.	34"	Engineered Laminate...

SPECIFICATIONS

SKU	LBNC4K1830
Working Load Limit (lbs.)	4,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Overall Length	34"
Spread	1.5' - 2.5'
Bail Dimensions	Inside Width: 3.8" Inside Length: 3" Top Thickness: 1" Thickness: 0.63"
Material	Engineered Laminate Wood
Finish	Lift lug powder coated safety yellow
Product Weight	67 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	17443
Additional Info	WLL (tons): 2 Headroom: 18" Lug Height: 9.2" Lug Thickness: 0.5"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/non-conductive-lifting-beam-4-000-lb-capacity-2-5-max-spread