

WIRE ROPE SLINGS > TYPE 215 MECHANICAL SPLICE GROMMETS

3/8" x 16' Mechanical Splice Grommet Wire Rope Sling

SKU: MSG-38-16 Item weight: 20 lbs

LENGTH	CAPACITY
16'	2.4 ton

SPECIFICATIONS

SKU	MSG-38-16
Safety Factor	5:1
30 Degree Capacity	2.4 ton
45 Degree Capacity	3.3 ton
60 Degree Capacity	4.1 ton
Vertical Capacity	2.4 ton
Choker Capacity	1.6 ton
Basket Capacity	4.7 ton
Diameter	3/8"
Length	16'
Body Diameter	3/8"
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/3-8-x-16-mechanical-splice-grommet-wire-rope-sling