

POLYESTER ROUND SLINGS > ENDLESS POLYESTER SLING

12' Domestic Endless Round Sling - Polyester | 25,000 lbs. Capacity

SKU: PRS8-12 Item weight: 15.6 lbs

|        |                             |
|--------|-----------------------------|
| LENGTH | CAPACITY                    |
| 12'    | 25,000 lbs. basket capacity |

SPECIFICATIONS

|                            |                                                                           |
|----------------------------|---------------------------------------------------------------------------|
| SKU                        | PRS8-12                                                                   |
| Safety Factor              | 5:1                                                                       |
| Rated for Overhead Lifting | Yes                                                                       |
| 30 Degree Capacity         | 25,000 lbs. basket capacity                                               |
| 45 Degree Capacity         | 35,400 lbs. basket capacity                                               |
| 60 Degree Capacity         | 43,300 lbs. basket capacity                                               |
| Vertical Capacity          | 25,000 lbs.                                                               |
| Choker Capacity            | 20,000 lbs.                                                               |
| Basket Capacity            | 50,000 lbs.                                                               |
| Length                     | 12'                                                                       |
| Body Diameter              | 2"                                                                        |
| Color                      | Orange                                                                    |
| Product Weight             | 15.6 lbs.                                                                 |
| Standards                  | Meets or exceeds all ASME B30.26 requirements.                            |
| Additional Info            | All Nylon and Polyester lifting slings have a length tolerance of +/- 2%. |

**SAFETY INFORMATION**

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability:** [heavyhaulrigging.com/p/endless-polyester-round-lifting-sling-12-orange\\_2](https://heavyhaulrigging.com/p/endless-polyester-round-lifting-sling-12-orange_2)