

LOAD CELLS > TENSION LOAD CELLS

Straightpoint® 25 T Radiolink Plus - RLP25T

SKU: RLP-25-T Item weight: 11 lbs

CAPACITY

55,000 lbs.

SPECIFICATIONS

SKU	RLP-25-T
Safety Factor	5:1
Load Capacity	55,000 lbs.
Pin Size	2"
Type	Standard Load Cell
Power Source	Handheld: 2 x AA batteries Loadcell: 4 x AA batteries
Accuracy	+/- 0.1% of Full Scale
Resolution	10 lbs.
Range	3,280'
Data Rate	3Hz - up to 200Hz can be ordered for dynamic load monitoring applications
Operating Temperature	-10° to +50°C 14° to 122° F
Battery Life	Handheld: 40 hours continuous Loadcell: 1,200 hours continuous
Display Type	240x128 Multi-Line Dot Matrix with Backlight
Product Weight	11 lbs.
Standards	IP67
Manufacturer Name	Crosby Straightpoint
Brand Part Number	RLP25T / 2789088

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/straightpoint-25-t-radiolink-plus-rlp25t