

WIRE ROPE > 6X19 GALVANIZED WIRE ROPE

3/8" 6x19 Galvanized Wire Rope - EIPS IWRC | 2,500' Coil

SKU: SC38EIG619-2500FT Item weight: 650 lbs

BREAK STRENGTH	GRADE	LENGTH
7.55 tons / 15,100 lbs.	EIPS	2,500'

SPECIFICATIONS

SKU	SC38EIG619-2500FT
Assembly Break Strength	7.55 tons / 15,100 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	3/8"
Length	2,500'
Wire Rope Class	6x19
Core	IWRC
Finish	Galvanized
Product Weight	650 lbs.
Weight Per Foot	0.26 lbs.
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Right Hand Regular Lay

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/3-8-6x19-galvanized-wire-rope-eips-iwrc-2-500-coil