

WIRE ROPE SLINGS > TYPE 110 SPELTER SOCKET

1-3/8" x 8' Closed and Closed Spelter Socket Wire Rope Sling

SKU: SPS-CSCS-1-38-8 Item weight: 120 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	LENGTH
38,400 lbs.	96 ton	8'

SPECIFICATIONS

SKU	SPS-CSCS-1-38-8
Working Load Limit (lbs.)	38,400 lbs.
Assembly Break Strength	96 ton
Safety Factor	5:1
Diameter	1-3/8"
Length	8'
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	WLL (tons): 19.2

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/1-3-8-x-8-closed-and-closed-splter-socket-wire-rope-sling