

WIRE ROPE SLINGS > TYPE 110 SPELTER SOCKET

3/4" x 16' Open and Open Spelter Socket Wire Rope Sling

SKU: SPS-OSOS-34-16 Item weight: 20 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	LENGTH
11,760 lbs.	29.4 ton	16'

SPECIFICATIONS

SKU	SPS-OSOS-34-16
Working Load Limit (lbs.)	11,760 lbs.
Assembly Break Strength	29.4 ton
Safety Factor	5:1
Diameter	3/4"
Length	16'
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	WLL (tons): 5.88

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/3-4-x-16-open-and-open-spelter-socket-wire-rope-sling