

LIFTING POINTS > STAINLESS STEEL HOIST RINGS

Actek 3/8"-16 x 1/2" Stainless Steel Hoist Ring - 500 lbs. WLL

SKU: SSHR-38-16-12-5-AC Item weight: 0.36 lbs

WORKING LOAD LIMIT	LENGTH	MATERIAL
500 lbs.	1/2" Bolt	316 Stainless Steel

SPECIFICATIONS

SKU	SSHR-38-16-12-5-AC
Working Load Limit (lbs.)	500 lbs.
Safety Factor	5:1
Rated for Overhead Lifting	Yes
Diameter	3/8" - 16 Bolt
Length	1/2" Bolt
Thread Type	UNC
Material	316 Stainless Steel
Torque	6 ft-lbs
Product Weight	0.36 lbs.
Standards	Meets or exceeds ASME B30.26 requirements.
Manufacturer Name	Actek®
Brand Part Number	AK58106

SAFETY INFORMATION
- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service. - Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking. - Protect webbing, rope and chain from sharp edges and corners with edge protection. - Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/actek-3-8-16-x-1-2-stainless-steel-hoist-ring-500-lbs-wll