

WIRE ROPE SLINGS > SINGLE LEG 6X19

5/16" x 16' Standard Eye Wire Rope Sling

SKU: SW1-516-16 Item weight: 2.88 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	16'	1 tons / 2,000 l...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW1-516-16
Safety Factor	5:1
30 Degree Capacity	1 tons / 2,000 lbs. Angled Basket Hitch
45 Degree Capacity	1.4 tons / 2,800 lbs. Angled Basket Hitch
60 Degree Capacity	1.7 tons / 3,400 lbs. Angled Basket Hitch
Vertical Capacity	1 tons / 2,000 lbs.
Choker Capacity	0.74 tons / 1,480 lbs.
Basket Capacity	2 tons / 4,000 lbs.
Grade	EIPS
Diameter	5/16"
Length	16'
Core	IWRC
End Fitting	Flemish Eye
Material	Bright Steel Wire Rope
Product Weight	2.88 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	Eye dimensions: 2-1/2"W x 5"L Rated capacities for basket hitch based on a D/d ratio of 25

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-single-leg-6x19-5-16-x-16