

WIRE ROPE SLINGS > EYE AND EYE HOOK WIRE ROPE SLING

1" x 12' Standard Eye & Hook Wire Rope Sling

SKU: SW1-E-EH-1-12 Item weight: 59.03 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	12'	9.8 tons / 19,60...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW1-E-EH-1-12
Safety Factor	5:1
30 Degree Capacity	9.8 tons / 19,600 lbs. Angled Basket Hitch
45 Degree Capacity	14 tons / 28,000 lbs. Angled Basket Hitch
60 Degree Capacity	17 tons / 34,000 lbs. Angled Basket Hitch
Vertical Capacity	9.8 tons / 19,600 lbs.
Choker Capacity	7.2 tons / 14,400 lbs.
Basket Capacity	19.6 tons / 39,200 lbs.
Grade	EIPS
Diameter	1"
Length	12'
Core	IWRC
End Fitting	Eye Hook & Standard Eye
Material	Bright Steel Wire Rope
Product Weight	59.03 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	Eye dimensions: 8"W x 16"L Rated capacities for basket hitch based on a D/d ratio of 25 10 ton carbon steel hook

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-single-leg-6x19-eye-and-eye-hook-1-x-12