

WIRE ROPE SLINGS > EYE AND EYE HOOK WIRE ROPE SLING

1/2" x 14' Standard Eye & Hook Wire Rope Sling

SKU: SW1-E-EH-12-14 Item weight: 11.93 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	14'	2.5 tons / 5,000...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW1-E-EH-12-14
Safety Factor	5:1
30 Degree Capacity	2.5 tons / 5,000 lbs. Angled Basket Hitch
45 Degree Capacity	3.6 tons / 7,200 lbs. Angled Basket Hitch
60 Degree Capacity	4.4 tons / 8,800 lbs. Angled Basket Hitch
Vertical Capacity	2.5 tons / 5,000 lbs.
Choker Capacity	1.9 tons / 3,800 lbs.
Basket Capacity	5 tons / 10,000 lbs.
Grade	EIPS
Diameter	1/2"
Length	14'
Core	IWRC
End Fitting	Eye Hook & Standard Eye
Material	Bright Steel Wire Rope
Product Weight	11.93 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	Eye dimensions: 4"W x 8"L Rated capacities for basket hitch based on a D/d ratio of 25 3 ton carbon steel hook

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-single-leg-6x19-eye-and-eye-hook-1-2-x-14