

WIRE ROPE SLINGS > THIMBLE AND THIMBLE WIRE ROPE SLING

1" x 8' Thimble Eye Wire Rope Sling

SKU: SW1-TH-TH-1-8 Item weight: 29.61 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	8'	9.8 tons / 19,60...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW1-TH-TH-1-8
Safety Factor	5:1
30 Degree Capacity	9.8 tons / 19,600 lbs. Angled Basket Hitch
45 Degree Capacity	14 tons / 28,000 lbs. Angled Basket Hitch
60 Degree Capacity	17 tons / 34,000 lbs. Angled Basket Hitch
Vertical Capacity	9.8 tons / 19,600 lbs.
Basket Capacity	19.6 tons / 39,200 lbs.
Grade	EIPS
Diameter	1"
Length	8'
Core	IWRC
End Fitting	Heavy-duty thimble
Material	Bright Steel Wire Rope
Product Weight	29.61 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	Thimble dimensions: 2-1/2"W x 4-1/2"L Rated capacities for basket hitch based on a D/d ratio of 25

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-single-leg-6x19-thimble-and-thimble-1-x-8