

WIRE ROPE SLINGS > THIMBLE AND THIMBLE WIRE ROPE SLING

3/8" x 3' Thimble Eye Wire Rope Sling

SKU: SW1-TH-TH-38-3 Item weight: 1.75 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	3'	1.4 tons / 2,800...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW1-TH-TH-38-3
Safety Factor	5:1
30 Degree Capacity	1.4 tons / 2,800 lbs. Angled Basket Hitch
45 Degree Capacity	2 tons / 4,000 lbs. Angled Basket Hitch
60 Degree Capacity	2.5 tons / 5,000 lbs. Angled Basket Hitch
Vertical Capacity	1.4 tons / 2,800 lbs.
Basket Capacity	2.8 tons / 5,600 lbs.
Grade	EIPS
Diameter	3/8"
Length	3'
Core	IWRC
End Fitting	Heavy-duty thimble
Material	Bright Steel Wire Rope
Product Weight	1.75 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	Thimble dimensions: 1-1/8"W x 2-1/8"L Rated capacities for basket hitch based on a D/d ratio of 25

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-single-leg-6x19-thimble-and-thimble-3-8-x-3