

WIRE ROPE SLINGS > 2 LEG BRIDLE

1/2" x 16' 2-Leg Wire Rope Bridle Sling with Eye Hooks

SKU: SW2-12-16 Item weight: 32.49 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	16'	2.5 tons / 5,000...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW2-12-16
Safety Factor	5:1
30 Degree Capacity	2.5 tons / 5,000 lbs.
45 Degree Capacity	3.6 tons / 7,200 lbs.
60 Degree Capacity	4.4 tons / 8,800 lbs.
Grade	EIPS
Diameter	1/2"
Length	16'
Core	IWRC
End Fitting	3 ton carbon steel hook
Material	Bright Steel Wire Rope
Product Weight	32.49 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	3/4" master link diameter Rated capacities for basket hitch based on a D/d ratio of 25

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-2-leg-bridle-1-2-x-16