

WIRE ROPE SLINGS > 4 LEG BRIDLE

1" x 12' 4-Leg Wire Rope Bridle Sling with Eye Hooks

SKU: SW4-1-12 Item weight: 276.07 lbs

|       |        |                    |                    |
|-------|--------|--------------------|--------------------|
| GRADE | LENGTH | CAPACITY           | MATERIAL           |
| EIPS  | 12'    | 20 tons / 40,00... | Bright Steel Wi... |

SPECIFICATIONS

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| SKU                | SW4-1-12                                                                                 |
| Safety Factor      | 5:1                                                                                      |
| 30 Degree Capacity | 20 tons / 40,000 lbs.                                                                    |
| 45 Degree Capacity | 28 tons / 56,000 lbs.                                                                    |
| 60 Degree Capacity | 34 tons / 68,000 lbs.                                                                    |
| Grade              | EIPS                                                                                     |
| Diameter           | 1"                                                                                       |
| Length             | 12'                                                                                      |
| Core               | IWRC                                                                                     |
| End Fitting        | 10 ton carbon steel hook                                                                 |
| Material           | Bright Steel Wire Rope                                                                   |
| Product Weight     | 276.07 lbs.                                                                              |
| Standards          | Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.                            |
| Additional Info    | 1-7/8" master link diameter Rated capacities for basket hitch based on a D/d ratio of 25 |

**SAFETY INFORMATION**

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability:** [heavyhaulrigging.com/p/wire-rope-sling-4-leg-bridle-1-x-12](https://heavyhaulrigging.com/p/wire-rope-sling-4-leg-bridle-1-x-12)