

WIRE ROPE SLINGS > TYPE 115 SWAGE SOCKET

3/4" x 12' Open and Open Swage Socket Wire Rope Sling

SKU: SWS-OSOS-34-12 Item weight: 20 lbs

|                    |                |        |
|--------------------|----------------|--------|
| WORKING LOAD LIMIT | BREAK STRENGTH | LENGTH |
| 11,760 lbs.        | 29.4 ton       | 12'    |

SPECIFICATIONS

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| SKU                       | SWS-OSOS-34-12                                                |
| Working Load Limit (lbs.) | 11,760 lbs.                                                   |
| Assembly Break Strength   | 29.4 ton                                                      |
| Safety Factor             | 5:1                                                           |
| Diameter                  | 3/4"                                                          |
| Length                    | 12'                                                           |
| Wire Rope Class           | 6x36WS                                                        |
| Standards                 | Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements. |
| Additional Info           | WLL (tons): 5.88                                              |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/3-4-x-12-open-and-open-swage-socket-wire-rope-sling](https://heavyhaulrigging.com/p/3-4-x-12-open-and-open-swage-socket-wire-rope-sling)