



BULK CHAIN > GRADE 120 TIE DOWN CHAIN ASSEMBLIES

# 3/8" x 20' Tie Down Chain with Eye Grab Hooks | Grade 120

SKU: TC3820120-PWG Item weight: 39 lbs

|                    |                |       |            |
|--------------------|----------------|-------|------------|
| WORKING LOAD LIMIT | BREAK STRENGTH | GRADE | CHAIN SIZE |
| 10,600 lbs.        | 42,400 lbs.    | 120   | 3/8"       |

## SPECIFICATIONS

|                            |                                                                                                    |
|----------------------------|----------------------------------------------------------------------------------------------------|
| SKU                        | TC3820120-PWG                                                                                      |
| Working Load Limit (lbs.)  | 10,600 lbs.                                                                                        |
| Assembly Break Strength    | 42,400 lbs.                                                                                        |
| Safety Factor              | 4:1                                                                                                |
| Rated for Overhead Lifting | No                                                                                                 |
| Grade                      | 120                                                                                                |
| Length                     | 20'                                                                                                |
| Chain Size                 | 3/8"                                                                                               |
| End Fitting                | Grab Hook                                                                                          |
| Material                   | High Strength Alloy Steel                                                                          |
| Finish                     | Powder Coated                                                                                      |
| Color                      | Blue                                                                                               |
| Operating Temperature      | 40°F / -40°C to 392°F / 200°C                                                                      |
| Product Weight             | 39 lbs.                                                                                            |
| Standards                  | DOT-compliant; meets or exceeds FMCSA CFR49 Section 393.104 and NACM requirements. AWRF Accredited |
| Manufacturer Name          | Pewag                                                                                              |
| Additional Info            | Items are made to order and most ship same day - exceptions apply to large orders.                 |

**SAFETY INFORMATION**

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- NOT FOR OVERHEAD LIFTING. This product is rated for cargo securement only.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability: [heavyhaulrigging.com/p/tie-down-chain-3-8-x-20-w-eye-grab-hooks-grade-120](https://heavyhaulrigging.com/p/tie-down-chain-3-8-x-20-w-eye-grab-hooks-grade-120)**