

BULK CHAIN > GRADE 80 BINDER CHAIN ASSEMBLIES

5/16" x 25' Tie Down Chain with Clevis Grab Hooks | Grade 80

SKU: TC5162580 Item weight: 28 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	GRADE	CHAIN SIZE
4,500 lbs.	18,000 lbs.	80	5/16"

SPECIFICATIONS

SKU	TC5162580
Working Load Limit (lbs.)	4,500 lbs.
Assembly Break Strength	18,000 lbs.
Safety Factor	4:1
Rated for Overhead Lifting	No
Grade	80
Length	25'
Chain Size	5/16"
End Fitting	Clevis Grab Hook
Material	Alloy Steel
Finish	Painted Chain
Product Weight	28 lbs.
Standards	DOT-compliant; meets or exceeds FMCSA CFR49 Section 393.104 and NACM requirements.
Manufacturer Name	KWB Chain / Import End Fittings
Additional Info	Made to order.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- NOT FOR OVERHEAD LIFTING. This product is rated for cargo securement only.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/tie-down-chain-assembly-5-16-x-25-w-clevis-grab-hooks-grade-80