

NYLON LIFTING SLINGS > BRIDLE SLINGS

1"x6' (2 ply) Triple Leg Nylon Sling w/ Master Link & Sewn Loop

SKU: TOE-EE2-901-06 Item weight: 9 lbs

WIDTH	LENGTH	CAPACITY
1"	6'	3,100 lbs.

SPECIFICATIONS

SKU	TOE-EE2-901-06
Safety Factor	5:1
30 Degree Capacity	3,100 lbs.
45 Degree Capacity	6,500 lbs.
60 Degree Capacity	8,000 lbs.
Width	1"
Length	6'
Sling Type	3-Leg Bridle
Plies	2
Product Weight	9 lbs.
Standards	Meets or exceeds all ASME B30.9 requirements.
Additional Info	All Nylon and Polyester lifting slings have a length tolerance of +/- 2%.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/1x6-2-ply-triple-leg-nylon-sling-w-master-link-sewn-loop