

NYLON LIFTING SLINGS > BRIDLE SLINGS

2"x4' (1 ply) Triple Leg Nylon Sling w/ Master Link & Sling Hook

SKU: TOS-EE1-902-04 Item weight: 9.42 lbs

|       |        |            |
|-------|--------|------------|
| WIDTH | LENGTH | CAPACITY   |
| 2"    | 4'     | 3,100 lbs. |

SPECIFICATIONS

|                    |                                                                           |
|--------------------|---------------------------------------------------------------------------|
| SKU                | TOS-EE1-902-04                                                            |
| Safety Factor      | 5:1                                                                       |
| 30 Degree Capacity | 3,100 lbs.                                                                |
| 45 Degree Capacity | 6,500 lbs.                                                                |
| 60 Degree Capacity | 8,000 lbs.                                                                |
| Width              | 2"                                                                        |
| Length             | 4'                                                                        |
| Sling Type         | 3-Leg Bridle                                                              |
| Plies              | 1                                                                         |
| Product Weight     | 9.82 lbs.                                                                 |
| Standards          | Meets or exceeds all ASME B30.9 requirements.                             |
| Additional Info    | All Nylon and Polyester lifting slings have a length tolerance of +/- 2%. |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/2x4-1-ply-triple-leg-nylon-sling-w-master-link-sling-hook](https://heavyhaulrigging.com/p/2x4-1-ply-triple-leg-nylon-sling-w-master-link-sling-hook)