

HIGH PERFORMANCE SLINGS > TWIN-PATH ENDLESS ROUNDSLINGS

14" x 16' Endless Twin-Path® High Performance Roundsling | Vertical Cap: 500,000 lbs.

SKU: TUFXKS50000-16 Item weight: 89.65 lbs

LENGTH	CAPACITY
16'	707,000 lbs.

SPECIFICATIONS

SKU	TUFXKS50000-16
Safety Factor	5.1
45 Degree Capacity	707,000 lbs.
60 Degree Capacity	866,000 lbs.
Vertical Capacity	500,000 lbs.
Choker Capacity	400,000 lbs.
Basket Capacity	1,000,000 lbs.
Length	16'
Minimum Connection Diameter	11.4"
Product Weight	89.65 lbs.
Additional Info	Nominal Body Width: 16" Minimum bending radius: 5.7" Tapered Body Width: 8"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/14-x-16-endless-twin-path-high-performance-roundsling-vertical-cap...](https://heavyhaulrigging.com/p/14-x-16-endless-twin-path-high-performance-roundsling-vertical-cap-500000-lbs)