

HIGH PERFORMANCE SLINGS > TWIN-PATH ENDLESS ROUND SLINGS

6" x 4' Endless Twin-Path® High Performance Roundsling  
| Vertical Cap: 85,000 lbs.

SKU: TUFXKS8500-4 Item weight: 3.3 lbs

|        |              |
|--------|--------------|
| LENGTH | CAPACITY     |
| 4'     | 120,190 lbs. |

SPECIFICATIONS

|                             |                                                                            |
|-----------------------------|----------------------------------------------------------------------------|
| SKU                         | TUFXKS8500-4                                                               |
| Safety Factor               | 5.1                                                                        |
| 45 Degree Capacity          | 120,190 lbs.                                                               |
| 60 Degree Capacity          | 147,220 lbs.                                                               |
| Vertical Capacity           | 85,000 lbs.                                                                |
| Choker Capacity             | 68,000 lbs.                                                                |
| Basket Capacity             | 170,000 lbs.                                                               |
| Length                      | 4'                                                                         |
| Minimum Connection Diameter | 1.84"                                                                      |
| Product Weight              | 3.3 lbs.                                                                   |
| Additional Info             | Nominal Body Width: 6" Minimum bending radius: .92" Tapered Body Width: 3" |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/6-x-4-endless-twin-path-high-performance-roundsling-vertical-cap-8...](https://heavyhaulrigging.com/p/6-x-4-endless-twin-path-high-performance-roundsling-vertical-cap-85000-lbs)