

RIGGING HOOKS > GALV. CARBON EYE HOIST HOOK W/ LATCH

Galvanized Carbon Eye Hoist Hook w/ Latch - 2 Ton

SKU: WCEHH2GV Item weight: 2.07 lbs

WORKING LOAD LIMIT	BREAK STRENGTH
4,000 lbs.	20,000 lbs.

SPECIFICATIONS

SKU	WCEHH2GV
Working Load Limit (lbs.)	4,000 lbs.
Assembly Break Strength	20,000 lbs.
Safety Factor	5:1
Finish	Galvanized
Product Weight	2.07 lbs.
Standards	Meets or exceeds ASTM A952 / A952M & ASME B30.10 requirements.
Additional Info	WLL (tons): 2

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/galvanized-carbon-eye-hoist-hook-w-latch-2-ton