

AUTO TIE DOWNS > WHEEL NETS

2" x 10' OEM Replacement Wheel Strap with 2 Wire Hooks and 3 Adjustable Rubber Cleats

SKU: WNTH42-10 Item weight: 2.45 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	LENGTH
3,333 lbs.	6,600 lbs.	10'

SPECIFICATIONS

SKU	WNTH42-10
Working Load Limit (lbs.)	3,333 lbs.
Assembly Break Strength	6,600 lbs.
Webbing Break Strength	12,000 lbs.
Diameter	Up to 36", No Minimum
Length	10'
End Fitting	Wire Hook / Double J-Hook
Color	Yellow
Product Weight	2.45 lbs.
Standards	AWRF Accredited
Additional Info	Webbing Width: 2"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/2-x-10-oem-replacement-wheel-strap-with-2-wire-hooks-and-3-adjust...